

Untitled

```
diagnostics
ntlm_auth: invalid option -- -
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

```
You MUST specify at least one Domain Controller.
You can use either \ or / as separator between the domain name and the controller
name
ntlm_auth: invalid option -- u
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

```
You MUST specify at least one Domain Controller.
You can use either \ or / as separator between the domain name and the controller
name
ntlm_auth: invalid option -- s
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

```
You MUST specify at least one Domain Controller.
You can use either \ or / as separator between the domain name and the controller
name
ntlm_auth: invalid option -- e
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

```
You MUST specify at least one Domain Controller.
You can use either \ or / as separator between the domain name and the controller
name
ntlm_auth: invalid option -- r
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

```
You MUST specify at least one Domain Controller.
You can use either \ or / as separator between the domain name and the controller
name
ntlm_auth: invalid option -- n
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
```

Untitled

-d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- a

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- m

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- e

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- =

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- a

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- m

unknown option: -?. Exiting

ntlm_auth usage:

Untitled

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- i

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- n

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- i

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- s

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- t

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

Untitled

```
ntlm_auth: invalid option -- r
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

```
ntlm_auth: invalid option -- a
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

```
ntlm_auth: invalid option -- t
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

```
ntlm_auth: invalid option -- o
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

```
ntlm_auth: invalid option -- r
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

```
ntlm_auth: invalid option -- -
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

Untitled

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- o

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- m

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- a

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- i

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- n

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- =

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED

Untitled

and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- c

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- a

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- r

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- i

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- e

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- n

unknown option: -?. Exiting

Untitled

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- s

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- c

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- h

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- o

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- o

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

Untitled

```
name
ntlm_auth: invalid option -- -
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

```
ntlm_auth: invalid option -- 1
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

```
ntlm_auth: invalid option -- 0
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

```
ntlm_auth: invalid option -- -
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

```
ntlm_auth: invalid option -- i
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

```
ntlm_auth: invalid option -- a
unknown option: -?. Exiting
ntlm_auth usage:
ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables
load-balancing among controllers -f enables failover among controllers (DEPRECATED
and always active) -l changes behavior on domain controller failyures to last-ditch.
-d enables debugging statements if DEBUG was defined at build-time.
```

Untitled

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- g

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- n

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- o

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- s

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- t

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- i

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables

Untitled

load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- c

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name

ntlm_auth: invalid option -- s

unknown option: -?. Exiting

ntlm_auth usage:

ntlm_auth [-b] [-f] [-d] [-l] domain\controller [domain\controller ...] -b enables load-balancing among controllers -f enables failover among controllers (DEPRECATED and always active) -l changes behavior on domain controller failyures to last-ditch. -d enables debugging statements if DEBUG was defined at build-time.

You MUST specify at least one Domain Controller.

You can use either \ or / as separator between the domain name and the controller name